



Upgrade to No Maintenance

with Graco's NEW Sealed 4-Ball Lower

Sealed Fluid Section

- Completely eliminates the need for TSL

Improved Durability

- Industry-leading design that continues pumping in the event of a bellows failure, giving you time to schedule maintenance
- NEW Ultralife Coatings on lower rods and cylinders – smoother finish vs. standard ceramic coatings results in better wear and longer seal life
- Redesigned Carbide Outlet Checks result in significantly longer life

Backwards Compatible with Most Legacy Graco Circulation Pumps

- Connection kits provide all components required to upgrade to the newest technology



Ordering Information

Sealed 4-Ball Lower

Part No.	Size	Output at 20 CPM	Maximum Working Pressure
17K656	750 cc	4.0 gpm (15 lpm)	460 psi (31.7 bar, 3.1 MPa)
17K657	1000 cc	5.3 gpm (20 lpm)	460 psi (31.7 bar, 3.1 MPa)
17K658	1500 cc	7.9 gpm (30 lpm)	460 psi (31.7 bar, 3.1 MPa)
17K659	2000 cc	10.6 gpm (40 lpm)	460 psi (31.7 bar, 3.1 MPa)

Connection Kits*

Part No.	Motor
17K523	President
17K525	E-Flo DC/NXT
17K517	Bulldog/Senator
17K524	E-Flo
17K519	Viscount I
17K520	Viscount II

**Connection Kits contain tie rods and adapters - all the components required to upgrade to a Sealed 4-Ball Lower. Refer to manual 311876 for complete information.*

Call Graco at 866.361.5929 or visit us at www.graco.com/finishing